PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: G11C 5/00, H03K 3/037

A1

(11) International Publication Number:

WO 97/40497

(43) International Publication Date:

30 October 1997 (30.10.97)

(21) International Application Number:

PCT/US97/06643

(22) International Filing Date:

18 April 1997 (18.04.97)

(30) Priority Data:

635,794

22 April 1996 (22.04.96)

us

(71) Applicant: UNITED TECHNOLOGIES CORPORATION [US/US]; Hamilton Standard Division, One Hamilton Road, Windsor Locks, CT 06096-1010 (US).

(72) Inventors: LAHEY, Michael, D.; 2075 Chapel Hills Drive, Colorado Springs, CO 80920 (US). HARRIS, Debra, S.; 2113 Winston Road, Colorado Springs, CO 80909 (US). GARDNER, Harry, N.; 1605 Bandedrock Court, Colorado Springs, CO 80919 (US). BARRY, Michael, J.; 16025 S.W. Colony Place, Tigard, OR 97224 (US).


(74) Agent: KELLY, Robert, H.; Intellectual Property Counsel, Hamilton Standard, One Hamilton Road, Windsor Locks, CT 06096-1010 (US). (81) Designated States: JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: HIGH RELIABILITY LOGIC CIRCUIT FOR A RADIATION ENVIRONMENT



(57) Abstract

According to the present invention, a dual memory cell, includes a first memory cell receiving a first logic state input signal and providing an output signal, and further includes a second memory cell receiving a second logic state input signal and providing an output signal, where the first and second memory cell and second memory cell further receive and respond to one or more logic signals from the other. The output signal of the first memory cells and the output signal of the second memory cell may be further combined to provide one resultant logic state output signal which has improved reliability in a radiation environment: